

Assembly Instruction Sheet #IS-1016P43 For Style 1016P43

Tools Required: Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.
Light Source: (3) E26 BULB MAX 60W/60 Bulb MAX 40W(Not Included)
Estimated Assembly Time: 10-20 minutes
Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

Warnings and Cautions
 Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety; it is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation. Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

<p>Package Contents</p> <p>B Middle Rod 4 1/2" 2pcs B2 6" 1pc BS 12" 5pcs A Fixture Body X1 C Ceiling Canopy X1</p>	<p>STEP 1 - Release Mounting bracket from Ceiling Canopy -</p> <p>Figure 1</p>															
<p>Hardware Contents</p> <table border="1"> <thead> <tr> <th>PART</th> <th>DESCRIPTION</th> <th>QUANTITY</th> </tr> </thead> <tbody> <tr> <td>BS</td> <td>Electrical Nuts</td> <td>2pcs</td> </tr> <tr> <td>CC</td> <td>Outlet Box Screw</td> <td>2pcs</td> </tr> <tr> <td>BS</td> <td></td> <td></td> </tr> <tr> <td>CC</td> <td></td> <td></td> </tr> </tbody> </table>	PART	DESCRIPTION	QUANTITY	BS	Electrical Nuts	2pcs	CC	Outlet Box Screw	2pcs	BS			CC			<p>STEP 2 - Install lamp arm to Fixture Body</p> <p>Figure 2</p>
PART	DESCRIPTION	QUANTITY														
BS	Electrical Nuts	2pcs														
CC	Outlet Box Screw	2pcs														
BS																
CC																

<p>STEP 3 - Install Rods, Ceiling Canopy to Fixture Body.</p> <p>Figure 3</p>	<p>STEP 6 - Install Ceiling Canopy to Ceiling</p> <p>Figure 6</p>
<p>STEP 4 - Attach Mounting bracket to Outlet Box</p> <p>Figure 4</p> <p>Supply Wire with Outlet Box Screws Ground Wire</p>	<p>STEP 7 - Install Bulbs.</p> <p>Figure 7</p>
<p>STEP 5 - Wire Connectors A. Use standard wire connectors to make all wire connections. Twist connectors until wires are tightly joined together. Wrap each connection with approved electrical tape and carefully stuff all the connected wires into the Outlet Box.</p> <p>Figure 5</p>	