

Assembly Instruction Sheet #IS-1063P 16 For Style 1063P16

Tools Required: Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.
Light Source: (1) 120V LED *42W DIMMABLE (3000K)
Estimated Assembly Time: 10-20 minutes
Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

⚠ Warnings and Cautions
 Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation. Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

Package Contents

1 Glass rod x35 2 Glass rod x35
 3 Glass rod x35 4 Glass rod x36
 A Fixture Body x1

| PART | DESCRIPTION | QUANTITY |
|------|------------------|----------|
| BB | Wire nut | 2pcs |
| CC | Outlet Box Screw | 2pcs |

Hardware Contents

BB Wire nut
 CC Outlet Box Screw

STEP 1 - Release Crossbar from Ceiling Canopy.

STEP 2 - Attach Crossbar to Outlet Box.
 A. Pass the supply wires through the Crossbar (EE). Attach the Crossbar (EE) to the Outlet Box (CC) with the head of the Green Ground Screw (not included). Secure it with Outlet Box Screws (not included). Tighten until snug.

Supply Wires with Outlet Box Screws Ground Wire
 EE
 CC
 Figure 2

STEP 3 - Wire Connections
 A. Use standard wire connectors (not included) to make all wire connections. Twist connectors and wires are tightly joined together. Wrap each connection with approved electrical tape and carefully stuff all the connected wires into the Outlet Box.

White wire from outlet box Wires from fixture
 Black wire from outlet box (or Red) Black wire from fixture
 Bare, or Green Ground wire from outlet box Ground wire from fixture
 Bare, or Green Ground wire from outlet box Ground wire from fixture
 Green Ground Screw on the Crossbar

STEP 4 - Install Ceiling Canopy to Ceiling

STEP 5 - Install Glass rod.

The glass rods are to be placed in no particular order / pattern