

Assembly Instruction Sheet #S-1212P16 For Style 1212P16

Tools Required: Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.
Light Source: (1) SUGGESTED LED G9 LED BAY SW (Not Included).
Individual Assembly Time: 16-30 minutes.
Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams before to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

Warnings and Cautions
 Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation. Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

Package Contents

- A** Fixture Body x1
- B** Middle Rod
- B1** 4"×2pos
- B2** 6"×1pos
- B3** 12"×3pos
- C** Glass shade x3
- D** Glass shade x1
- E** Metal shade x2

Hardware Contents

PART	DESCRIPTION	QUANTITY
AA	Decorative Caps	4pos
BB	Mounting Screws	4pos
CC	Outlet Box Cover	1pos
DD	Mounting Screws	4pos
EE	Mounting Screws	4pos
FF	Lock Washer	1pos
GG	Lock Nut	1pos

