

Assembly Instruction Sheet #S-1246W5 For Style 1246W5

Tools Required: Flathead screwdriver, Philips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.

Light Source: (1) 120V LED 9W DIMMABLE (3000K)


Estimated Assembly Time: 15-30 minutes

Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams before to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

⚠ Warnings and Cautions

Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation. Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.


Package Contents



1 Glass tube x 1

A Fixture Body x1

Hardware Contents		
PART	DESCRIPTION	QUANTITY
BB	Wire nut	2pcs
CC	Screw	2pcs



STEP 1 - Release Mounting bracket from Ceiling Canopy.




Figure 1

STEP 2 - Attach Mounting bracket to Outlet Box

Attach the supply wires through the Mounting bracket (EE) with the Mounting bracket (EE) to the Outlet Box. Secure it with Outlet Box Screws. Tighten until snug.




Figure 2

STEP 4 - Install Ceiling Canopy to Ceiling




Figure 4

STEP 3 - Wire Connections




Figure 3

STEP 5 - Install tube.




Figure 5