

# Assembly Instruction Sheet #IS-5523p22c

## For Style 5523p22c

**Tools Required:** Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.  
**Light Source:** (8) G9 40W Maximum(Not Include).

**Estimated Assembly Time:** 10-20 minutes

**Preparation:** Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

### Warnings and Cautions


Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation. Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

### Package Contents

- [B] Middle Rod**
  - B1 4\*\*2pcs
  - B2 6\*\*1pcs
  - B3 12\*\*5pcs
- [A] Fixture Body x1**
- [C] Ceiling Canopy X1**
- 25mmX1PCS
- 14mmX12PCS
- 14mmX15PCS
- 95mmX1PCS
- 25mmX1PCS
- 25mmX1PCS
- [1] Crystal x32**
- 14mmX4PCS
- 95mmX1PCS
- 95mmX1PCS
- [4] Crystal x13**
- [5] Crystal x6**
- [2] Crystal x26**
- 14mmX8PCS
- 14mmX16PCS
- 25mmX1PCS
- 25mmX1PCS
- 95mmX1PCS
- 95mmX1PCS
- [3] Crystal x20**
- [6] Crystal x1**

### Hardware Contents

PART	DESCRIPTION	QUANTITY
BB	Wire nut	2pcs
CC	Screw	2pcs



### STEP 1- Release Crossbar from Ceiling Canopy .




Figure 1

### STEP 2 - Install Rods to Fixture Body




Figure 2

### STEP 3 - Attach Mounting bracket to Outlet Box

A. Pass the supply wires through the Mounting bracket (EE). Attach the Mounting bracket (EE) to the Outlet Box with the head of the Green Ground Screw facing you. Secure it with Outlet Box Screws (CC). Tighten until snug.




Figure 3

### STEP 5 - Install Ceiling Canopy to Ceiling





Figure 5

### STEP 4 - Wire Connections

A. Use standard wire connectors to make all wire connections. Twist connectors until wires are tightly joined together. Wrap each connection with approved electrical tape and carefully stuff all the connected wires into the Outlet Box.

White wire from outlet box




White wire from fixture

Black wire from outlet box (or Red)




Black wire from fixture

Bare, or Green Ground wire from outlet box



Ground wire from fixture

Bare, or Green Ground wire from outlet box



Ground wire from fixture

Green Ground Screw on the Crossbar

Figure 4

### STEP 6 - Install Crystal and Bulbs.




Figure 6